

# DX Units

Dimensions			Air Flow	Power Supply	COP Heat	COP Cool	Heating Capacity	Cooling Capacity	Model
L	H	D							
110	110	115	1200	380V/3PH/50Hz	3.1	2.8	40000	38200	<a href="#">RN 40P</a>
110	110	115	1200	220V/1PH/50Hz	3.1	2.8	40000	38200	<a href="#">RN 40P -1</a>
110	110	115	1600	380V/3PH/50Hz	2.9	2.7	50400	47800	<a href="#">RN 49P</a>
110	110	139	2000	380V/3PH/50Hz	3.1	2.8	62200	60000	<a href="#">RN 60P</a>
110	110	139	2500	380V/3PH/50Hz	2.9	2.7	74900	73600	<a href="#">RN 72P</a>
130	130	142	3200	380V/3PH/50Hz	3.1	3	99600	98000	<a href="#">RN 96P</a>
145	150	142	4000	380V/3PH/50Hz	2.9	2.7	123200	121000	<a href="#">RN 120P</a>

## DX Units » Package

Model	Cooling Capacity	Heating Capacity	COP Cool	COP Heat	Power Supply	Air Flow	Dimensions		
							D	H	L
<a href="#">RN 40P</a>	38200	40000	2.8	3.1	380V/3PH/50Hz	1200	115	110	110
<a href="#">RN 40P -1</a>	38200	40000	2.8	3.1	220V/1PH/50Hz	1200	115	110	110
<a href="#">RN 49P</a>	47800	50400	2.7	2.9	380V/3PH/50Hz	1600	115	110	110
<a href="#">RN 60P</a>	60000	62200	2.8	3.1	380V/3PH/50Hz	2000	139	110	110
<a href="#">RN 72P</a>	73600	74900	2.7	2.9	380V/3PH/50Hz	2500	139	110	110
<a href="#">RN 96P</a>	98000	99600	3	3.1	380V/3PH/50Hz	3200	142	130	130
<a href="#">RN 120P</a>	121000	123200	2.7	2.9	380V/3PH/50Hz	4000	142	150	145